



LAVOR PRO PRODUCT UPDATE

HOT STATIC HIGH PRESSURE CLEANER HHP

Dear Customers,
 We presented HHP at PULIRE Verona last June and it was a huge success because it can really solve any cleaning problems with an incomparable competitive price!

Below you find some useful suggestions of use and application:



And now some technical data and prices of the various models, painted or stainless steel:

Model	HHPV 1211 LP RA	HHPV 1515 LP RA	HHPV 2015 LP RA	HHPV 2021 LP RA
Code	8.624.0601	8.624.0602	8.624.0603	8.624.0604
operat. pressure/max	30÷120 bar	30÷150 bar	30÷200 bar	30÷200 bar
operat. pressure/max	330÷660 l/h	450÷900 l/h	450÷900 l/h	630÷1260 l/h
abs. power/voltage	3000W-230V-50Hz	5000W-400V-50Hz	7300W-400V-50Hz	9700W-400V-50Hz
diesel tank/detergent tank	20/20 l.	20/20 l.	20/20 l.	20/20 l.
max temp. inlet/outlet	40 °C / 140 °C	40 °C / 140 °C	40 °C / 140 °C	40 °C / 140 °C
fuel consumption/heat output	4,72 l/h-58kW	4,72 l/h-58kW	4,72 l/h-58kW	6,6 l/h-88kW

Available also stainless steel models: aside codes and prices	HHPX 1211 LP RA	HHPX 1515 LP RA	HHPX 2015 LP RA	HHPX 2021 LP RA
	8.624.0609	8.624.0610	8.624.0611	8.624.0612

STAINLESS STEEL



HOT STATIC HIGH PRESSURE CLEANER HHP



Painted or stainless steel structure, waterproof against weather condition and fixable to the ground.

Always ready to the use and protect against undesired operation.

The various options possibilities are: temperature insulation and inner heating with thermostat, coin machine, flame control, self retractable high pressure hose reel and high pressure hose twisting support.

Water cooled motor with elastic joint to the crankshaft pump with brass head and of great dimensions.

The detergent delivery is in high pressure through a dose pump with fine regulation.

Safety controls: delayed low tension automatic stop , leak detection, water and operator presence control.



The control panel is protected from undesired use and switch on main power, hot water and detergent distribution

Model	HHPV 1211 LP RA	HHPV 1515 LP RA	HHPV 2015 LP RA	HHPV 2021 LP RA
Code	8.624.0601	8.624.0602	8.624.0603	8.624.0604
operat. pressure/max	30÷120 bar	30÷150 bar	30÷200 bar	30÷200 bar
operat. pressure/max	330÷660 l/h	450÷900 l/h	450÷900 l/h	630÷1260 l/h
abs. power/voltage	3000W-230V-50Hz	5000W-400V-50Hz	7300W-400V-50Hz	9700W-400V-50Hz
diesel tank/detergent tank	20/20 l.	20/20 l.	20/20 l.	20/20 l.
max temp. inlet/outlet	40 °C / 140 °C	40 °C / 140 °C	40 °C / 140 °C	40 °C / 140 °C
fuel consumption/heat output	4,72 l/h-58kW	4,72 l/h-58kW	4,72 l/h-58kW	6,6 l/h-88kW

PRICE LIST

ACCESSORIES

Below you find a list of all optional accessories you can order together with the product:

Code	Picture	Description	PRICE LIST
At product order time	-	Complete installed internal insulation	
At product order time	-	Timer coin or token (not included) machine	
6.608.0025	-	Internal heating frost protection with thermostat	
6.608.0026	-	Flame sensor kit	
6.608.0029	-	Remote control kit	
6.608.0032		Twisting pole kit for HP hose	
6.608.0034		Retractable wall mount painted hose reel set (hose not included)	