



HHPV LP



Standard equipment:

- 6.601.0001 Gun PRO S'10 3/8" M with quick connection



- 6.602.0043 Lance 900 mm with quick connection.



- 3.103.0050 Nozzle type 045 (mod. 1211 LP)
- 3.103.0051 Nozzle type 050 (mod. 2015 LP)
- 3.103.0056 Nozzle type 075 (mod. 2021 LP)



- 4.618.0143 High pressure hose 10 m



- Power cable 5 m

Optional:

- Rotating Booms code. 6.608.0032
- Flame sensor kit code. 6.608.0026
- Remote control kit code. 6.608.0029
- Low temperature internal insulation protection/heating
- With header tank and anti scale device

Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling.
- Three ceramic pistons, brass linear pump head with built-in by-pass valve.
- Integrated elastic joint, for best pump coupling.
- Low voltage and delayed Total Stop.
- Suction and delivery S/S valves.
- Vertical burner with high thermal efficiency steel coil.
- Header tank.
- High pressure detergent dosing pump.
- Control panel with protection cover.
- Accessory holder.
- S/S fixing base support.
- Varnished steel structure.
- Rotating booms (**optional**).



	HHPV 1211 LP	HHPV 2015 LP	HHPV 2021 LP
code	8.624.0601	8.624.0603	8.624.0604
operat. pressure	120 bar-1740 psi	200 bar-2900 psi	200 bar-2900 psi
delivery rate	660 l/h-2.91 GPM	900 l/h-3.96 GPM	1260 l/h-5.55 GPM
abs. power/voltage	3000W - 230V~50Hz 1ph	7300W - 230V~50Hz 1ph	9700W - 400V~50Hz 3 ph
motorpump type/RPM	MP3/1450 RPM	MPW5/1450 RPM	MPW5/1450 RPM
max. temp. inlet/outlet	40/140 °C	40/140 °C	40/140 °C



HHPX-RCS

Environmental friendly

Electric boiler: no emissions in the environment, very low set up and service cost



With the new radio control system

Standard equipment:

- 6.601.0003 Gun PRO S'10 3/8 M with radio control



- 6.602.0044 Lance 900 mm with quick connection.



- 3.103.0017 Nozzle type 2505



- 4.618.0143 High pressure hose 10 m



Optional:

- Rotating Booms
- Detergent function for rims
- Set of 200 coins
- Wall mount hose-reel (hose not included)
- Osmosis system additional inlet
- Low temperature internal insulation protection
- Lance holder
- Floor lance holder
- Softener kit
- Electronic coin operating system

Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling.
- Three ceramic pistons, nickel-plated linear pump head with built-in by-pass valve.
- 6,7Kw electric boiler with S/S body.
- No emissions in the environment, very low set up and service cost.
- 2 tanks, detergent and wax regulator., mechanical coin operating system and 4 washing programs: 1 prewash cycle with shampoo, 2 HP washing, 3 Wax, 4 Final rinse.
- Gun with RC system: with the new Radio Control system it is possible to choose among different washing programs directly from the gun without stopping the cleaning task and saving a lot of time.
- Possibility to add modules for use of softened or demineralized water or osmosis system set (optional). S/S structure

	HHPX-RCS
code	8.629.0006
operat. pressure	120 bar-1740 psi
delivery rate	660 l/h-2.91 GPM
abs. power/voltage	9700W - 400V~50Hz 3ph
motorpump type/RPM	MPW3/1450 RPM
max. temp. inlet/outlet	40/60 °C